PART NO. 25445

Instruction Sheet TOYOTA REPLACEMENT CAMBER/CASTER CAM KIT

This part should only be installed by personnel who have the necessary skill, training and tools to do the job correctly and safely. Incorrect installation can result in personal injury, vehicle damage and / or loss of vehicle control.


- 1. Before beginning alignment, inspect for loose or worn parts and replace as necessary, check tire pressure, and look for odd tire wear.
- 2. Raise front of vehicle and properly support it by frame.
- 3. Pre-assemble SPC cam assemblies by first installing a 80002003 cam and then a tube spacer on each bolt.
- 4. One at a time, remove original cam assemblies from lower control arm and replace them with the SPC assembly, installing new assemblies as shown in Figure 1. The longer of the two bolts is used in the rear location.

SPC tool 40915 may help with removal of OEM cams. However, if tubes are solidly seized in bushings, you may not be able to remove them. To achieve camber/ caster change, you may need to replace upper control arms with SPC Part No. 25485.

Note: The rear cams of the control arm are trapped in vehicle by the steering rack. To avoid removing rack, drive them rearward as far as possible and cut off protruding part of sleeve. This should allow the rest of the sleeve to be driven out. Install SPC cam kit from the front as shown in Figure 1.

- 5. Install remaining cam and nut on each bolt and loosely tighten.
- 6. Lower vehicle, jounce suspension, and use cams to adjust alignment to desired settings by turning the
- bolt. 7. Hold head of bolt and tighten
- nut to 150 ft-lb to lock settings. Always check for proper clearance between suspension components and other components of
- 8. Adjust toe and road test vehicle.

the vehicle.





Specialty Products Company

P.O. Box 923 • Longmont, CO 80502 • (303) 772-2103 • Fax: (303) 772-1918 www.specprod.com • www.spcperformance.com • Email:info@specprod.com Toll Free Technical Hot Line: 1-800-525-6505